



**JETPRINT's Quality Standard for Compatible Toner Cartridge**

Description				
No.	Item	Description	Acceptability	Measurement
1	SAD	Image density in print area	>1.35	Densometer
2	Uniformity	Uniformity of image density	< 0.08	Densometer
3	Background	Background in the blank area	< 0.08	Densometer
4	White dots in black version	= 0.2-0.4 mm dia.	< 0.08	Densometer
		> 0.4 mm dia.	≤6 dots	
		= 0.2 mm dia.	≤3 dots	
		> 0.2 mm dia.	≤4 dots	
5	Black dots in white version	Horizontal or Vertical stripe in black version	≤3 dots	By eye or Standard Comparison version
6	White&black line in black version	Horizontal or Vertical stripe in white version	Not allowed	By eye
7	Black line in white version	Voiding in imaging area	Not allowed	By eye
8	Voiding	Cyclic malfunction caused by OPC, MR or PCR	Not allowed in normal A4 papers	By eye or Quality Comparison version
9	Repeating defects	Ghosting of letterform or imaging	Not allowed	
10	Ghosting	Tested according to ASTM standard (5% "E" version)	≤ 2 grade	
11	Yield		≥95%OEM	Printing test



Stournari 53, Athens 104 32, Greece

Tel/Fax: +30 210 5228 377 & 5228 340

[www.jetprint.gr](http://www.jetprint.gr)